



FLESSY

A SHOW ON DISPLAY

TECHNICAL SPECIFICATIONS

- Electrical supply: 220-240V; 50/60HZ
- Internal electrical supply: 0.55 kW

TEMPERATURE AND REFRIGERATION MANAGEMENT

- Tropicalized refrigerator unit.
- Management of different temperature profiles in accordance with the new classes required by regulations:
category 2: whole machine with temp. < 12°C
category 3: whole machine with temp. < 3°C
category 4: 50% of the machine with temp. < 12°C and 50% with temp. < 3°C
- Safety device to control the temperature and block the spirals if the regulatory conditions for perishable products are not met.
- Easily accessible and removable refrigeration unit.
- The dust filter is easy to extract, making maintenance easier.
- Refrigerant gas: R290

ENERGY EFFICIENCY SOLUTIONS

- 40 mm foam-lined compartment with PVC thermal break between inside and outside.
- Ample 20 mm low-emission pyrolytic tempered double glazing.

- Anti-theft and insulated product delivery door “push”.
- Frontal air intake.
- Air deflector that allows you to manage several zones at different temperatures and reduce energy consumption through better cold management.
- Energy Saving Mode: management of the Led lighting on/off, during specified time slots.
- In compliance with *ROHS* and *WEEE*.

DRAWER LAYOUT MANAGEMENT

- Adjustable layout: 7.5 mm pitch between the fixing holes of the drawer guides for a more flexible internal configuration.
- Kit supplied:
 - XL version: 10 product holders and 30 spiral ejectors.
 - L and M slave versions: 8 product holders and 24 spiral ejectors.
 - M master version: 6 product holders and 18 spiral ejectors.
- Versions available with touch interface accessible to PMRs

PAYMENT SYSTEM

- Only master models can accommodate all the main payment systems based on Executive and MDB protocols.

FLESSY XL VERSIONS	Master / slave	Touch 7"	Drawers* / spirals	Selections / capacity	Leds on each drawer	Products drop sensor	Luminous pathway	Digital price display	Side compartment with 2 distribution columns	Energy class
FLESSY XL + 6-53 MA	master	■	6 / 10	53/425	■	■	■		68 pet 50cl	D
FLESSY XL + 6-53 MA DISP	master	■	6 / 10	53/425	■	■	■	■	68 pet 50cl	D
FLESSY XL 6-53 MA	master	■	6 / 10	53/425	■	■	■			C
FLESSY XL 6-53 MA DISP	master	■	6 / 10	53/425	■	■	■	■		D
Dimensions mm	H 1830 x W 1086 x D 830									
Weight	version XL PLUS 347 kg / version XL 312 kg									

** Can also contain 102 standard or slim 33cl cans with the respective optional kits

FLESSY L VERSIONS

FLESSY L VERSIONS	Master / slave	Touch 7"	Drawers* / spirals	Selections / capacity	Leds on each drawer	Products drop sensor	Luminous pathway	Digital price display	Side compartment with 1 distribution column	Energy class
FLESSY L + 6-44 MA	master	■	6 / 8	44/356	■	■	■		34 pet 50cl	D
FLESSY L + 6-44 MA DISP	master	■	6 / 8	44/356	■	■	■	■	34 pet 50cl	D
FLESSY L 6-44 MA	master	■	6 / 8	44/356	■	■	■			C
FLESSY L 6-44 MA DISP	master	■	6 / 8	44/356	■	■	■	■		D
FLESSY L 6-44 SL	slave		6 / 8	44/356	■	■				C
FLESSY L 6-44 SL DISP	slave		6 / 8	44/356	■	■		■		D
Dimensions mm	master H 1830 x W 870 x D 830 / slave H 1830 x W 715 x D 830									
Weight	version L PLUS MA 275 kg / version L MA 250 kg / version L SL 210 kg									

* Configurable with up to 7 drawers on XL and L versions, on request / It can also contain 51 standard or slim 33cl cans with the respective optional kits

FLESSY M VERSIONS

FLESSY M 6-34 MA	master	■	6 / 6	34/292	■	■				D
FLESSY M 6-44 SL	slave		6 / 8	44/356	■	■				D
Dimensions mm	H 1700 x L 715 x P 830									
Weight	version M MA 215 kg / version M SL 210 kg									